

Product Data Sheet

NOTE: The information in this publication is the result of careful testing in our laboratories, complemented by selected literature. It does not in any way constitute a guarantee, nor does it serve as a license to operate any patent. Due to widely varying conditions of product use, which are beyond our control, it is strongly recommended that the product be tested for suitability. Product typical properties in this publication are current.

DELTASYN ULTRA SAE 10W-40

DeltaSyn Ultra SAE 10W-40 is a HC-Synthetic high performance motor oil for diesel engines of the newest generation. It was specially developed for diesel engines with EURO 5 and EURO 6 standard with aftertreatment of exhaust gas (particle separator). In order to maintain the functionality of aftertreatment systems and to avoid disturbance, the use of a motor oil with Low SAPS (Low Ash) technology is obligatory.

DeltaSyn Ultra SAE 10W-40 can also be used for diesel engines with Euro 4 and engines with particulate fi lters in combination with low-sulfur diesel (up to 50 ppm). The reduced values of sulphate, phosphor and sulphur are guaranteed by selection of specially developed basic oils and additives.

DeltaSyn Ultra SAE 10W-40 meets and exceeds with the following manufacturers specifications:

API CK-4/CJ-4/CI-4/SN	ACEA E6-, E7-, E9-08
MB-228.51, (226.9)	MAN M 3477, M 3271-1
VOLVO VDS-3 , CNG	CATERPILLAR ECF-1a
CUMMINS CES 20076/77	DAF Long drain
DEUTZ DQC-IV-10 LA	JASO DH-2; MTU Typ 3.1
MACK EO-N / EO-M Plus	RVI (Renault) RLD-2, RXD, RGD
SCANIA Low Ash	ALISON TES 439

Physical Properties

PRODUCTS	10W-40
SAE Grade	10W-40
Viscosity:	
@ -25°C, mPa.s	6800
@ 100°C, cSt	15.3
Viscosity Index	150
Specific Gravity	0.872
Flash Point, °C	232
Pour Point, °C	-32
Total Base #, mg KOH/g	11.3

Shelf Life: DeltaSyn Ultra 10W40 product have a 5 years shelf life. Shelf life is from the date of manufacture, after which the product should be recertified prior to use.