

Product Data Sheet

NOTE: The information in this publication is the result of careful testing in our laboratories, complemented by selected literature. It does not in any way constitute a guarantee, nor does it serve as a license to operate any patent. Due to widely varying conditions of product use, which are beyond our control, it is strongly recommended that the product be tested for suitability. Product typical properties in this publication are current.

DELTA MARINE

Delta Marine is a highly effective diesel engine oil developed for use in trunk piston engines operating on low sulphur fuels in marine and industrial applications.

Delta Marine is produced with the use of an advanced and balanced additive package which allows to have excellent resistance to oxidation and viscosity increase over a long period of service. It has a superior water separating properties and provide excellent corrosion protection.

Delta Marine is formulated with base oils having proven successful performance in diesel engines. The additive system is balanced to provide excellent resistance to thermal degradation under moderately severe operating conditions. They also provide good engine cleanliness and superior wear protection.

Physical Properties

PRODUCT	Delta Marine
SAE Grade	40
Viscosity:	
@ 40 °C, mm ² /s	142
@ 100°C, mm ² /s	145
Ash, Sulfated, wt%,	2.1
Viscosity Index	100
Specific Gravity 15.6 C/15.6 C	0.899
Flash Point, °C	272
Pour Point, °C	-9
Total Base #, mg KOH/g	15

Shelf Life: Brautek Delta Marine have a 5 years shelf life. Shelf life is from the date of manufacture, after which the product should be recertified prior to use.