

Product Data Sheet

Manufactured by Klüber Lubrication NA LP • P.O. Box 131359 • Tyler, CR 2120, Texas 75713, under license from Brautek LLC

NOTE: The information in this publication is the result of careful testing in our laboratories, complemented by selected literature. It does not in any way constitute a guarantee, nor does it serve as a license to operate any patent. Due to widely varying conditions of product use, which are beyond our control, it is strongly recommended that the product be tested for suitability. Product typical properties in this publication are current.

SYN AIR PRESS DSO SERIES

Syn Air Press DSO synthetic lubricants are unique combinations of quality diester base stocks and the latest additive technology.

Brautek provides a wide range of Syn Air Press DSO lubricants that cover applications for rotary vane, rotary screw, and all ages and design types of reciprocating compressors.

Syn Air Press DSO lubricants are especially noted for the following benefits:

- *Low temperature fluidity*
- *Better thermal conductivity-reduces operating temperature*
- *Reduced friction – approximately 20% lower coefficient of friction.*
- *High temperature thermal stability will not disassociate under thermal stress.*
- *Greater resistance to mechanical stress will not shear under heavy loads or extreme stress.*
- *Reduced metal-to-metal wear-polar properties provided better metal wetting*
- *Better demulsibility characteristics-moisture separates readily, providing better rust and corrosion protection.*
- *More energy efficiency.*

These lubricants are designed for use in the crankcase and as a cylinder lubricant. They are compatible with almost all elastomers used in compressors and pumps, including paint used in crankcases.

COMPATIBILITY:

The following materials are compatible for use with Syn Air Press DSO lubricants:

Epoxy Paint, Celcon, Viton®, High Nitrile Rubber (Buna N, NBR-greater than 36% Acrylonitrile), Medium Nitrile Rubber (Buna N, NBR 30-36% Acrylonitrile), Teflon®, Oil Resistant Alkyd, and Nylon.

Syn Air Press DSO-100 is recommended for use in the following applications:

Reciprocating compressors, Rotary vane compressors, Ball and roller bearings. Low temperature lubrication High temperature lubrication General lubrication for applications requiring an ISO 100 lubricant.

Syn Air Press DSO-125 and Syn Air Press DSO-150 are recommended for the following applications:

Reciprocating compressors, Rotary vane compressors, Ball and roller bearings. Low temperature lubrication High temperature lubrication General lubrication for applications requiring an ISO 150 lubricant.

Syn Air Press DSO-32 is recommended for use in the following applications:

Centrifugal Compressors, Certain rotary screw & vane compressors. Low temperature lubrication High temperature lubrication General lubrication for applications requiring an ISO 32 lubricant.

Syn Air Press DSO-68 is recommended for use in the following applications:

Rotary screw and vane compressors, Ball and roller bearings. Low temperature lubrication, High temperature lubrication, Mist lubrication systems, General lubrication for applications requiring an ISO 68 lubricant

Product Data Sheet

NOTE: The information in this publication is the result of careful testing in our laboratories, complemented by selected literature. It does not in any way constitute a guarantee, nor does it serve as a license to operate any patent. Due to widely varying conditions of product use, which are beyond our control, it is strongly recommended that the product be tested for suitability. Product typical properties in this publication are current.

SYN AIR PRESS DSL SERIES (Diester) Physical Properties

PRODUCTS	DSO-32	DSO-46	DSO-68	DSO-100	DSO-125	DSO-150
ISO Grade	32	46	68	100	125	150
Viscosity:						
@ 40°C, cSt	30.5	42.0	64.0	97.0	125	154
@ 100°C, cSt	4.90	5.74	8.30	10.8	13.3	15.5
Viscosity Index	73	66	97	94	103	101
Specific Gravity	0.941	0.965	0.964	0.961	0.957	0.956
Density lbs/gal	7.837	8.037	8.037	8.008	7.975	7.962
Pour Point, °F(°C)	-65 (-54)	-65 (-54)	-40 (-40)	-30 (-34)	-38 (-39)	-30 (-34)
Flash Point, °F(°C)	490 (254)	475 (246)	490 (254)	495 (257)	495 (257)	505 (263)
Autoignition Point ;F(°C)	765 (407)	720 (373)	765 (407)	780 (416)	785 (418)	785 (418)
Copper Corrosion	1A	1A	1A	1A	1A	1A

SPECIAL NOTE: Syn Air Press DSO lubricants are not compatible with some elastomers used in compressors and pumps including some paint used in cranks. Consult the Material Compatibility Guide for specific recommendations.

SYN AIR PRESS DSO (Diester)

SYNTHETIC AIR COMPRESSOR

Shelf Life: SYN AIR PRESS DSO-125 & DSO-150 have a 5 year shelf life, all other SYN AIR PRESS DSO Series products have a 5 years shelf life. Shelf life is from the date of manufacture, after which the product should be recertified prior to use.