

Product Data Sheet

NOTE: The information in this publication is the result of careful testing in our laboratories, complemented by selected literature. It does not in any way constitute a guarantee, nor does it serve as a license to operate any patent. Due to widely varying conditions of product use, which are beyond our control, it is strongly recommended that the product be tested for suitability. Product typical properties in this publication are current.

SYNCROWN HD

SynCrown HD is a synthetic gear lubricant, specially designed for heavy duty automotors gearboxes, used in severe conditions of operation and where an EP lubricant is not required.

SynCrown HD is formulated using synthesized hydrocarbon fluid and exclusive additives to enhance oxidation resistance and provide maximum protection against wear, rust and corrosion, resulting in extended drain.

Application

- Gearboxes in severe operating conditions
- Gearboxes where a lubricant without extreme properties is required Pressure.
- Heavy Duty Equipment Gear Boxes.

Characteristics

SynCrown HD meets or exceeds API MT-1, Eaton Transmisión Div. PS-386, Mack Truck TO-A PLUS, International Truck TMS 6816, Zf Freedomline, Viscosidad SAE 50

Physical Properties

PRODUCTS	SAE 50
ISO Grade	50
Viscosity	
@ 40°C, cSt	132
@ 100°C, cSt	17.5
Viscosity Index	146
Flash Pt. F°(C°)	230

Shelf Life: Product shelf life is 5 years from the date of manufacture, after which the product should be recertified prior to use